

LXS-WHT-67953BIUF

SPECIFICATION DATA SHEET

PRODUCT DETAILS						
Manufacturer :	Artize	Туре:	Wall hung WC (water closet)			
Range	Lexa	Flush valves	Regular, Dual & I Flush advantages			
Colour:	White	Material:	Ceramic - Vitreous China			
Outlet	Vertical	BOM doc.NO.	ASW/09/2018/46			
	Internal diameter of inlet hole Ø 55 +2 -1 mm					


Technical Details: External diameter of outlet hole Ø 100 +5 -2 mm


ARTICLE NAME: WALL HUNG WC






TECHNICAL DIMENSIONS







TOP VIEW

SIDE VIEW

BACK VIEW

ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP				
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)					
375	530	330	26.5	Rimless WC, Blind Installation with quick release seat cover, Exclusive Design				

ACCESSORIES PROVIDED				
UF soft close seat cover	LXS-WHT-67103			
Fixing Kit	LES-WHT-1206			
ACCESSORIES RECOMMENDED				
Rag bolt	ZPS-SNS-RB07			
Concealed cistern model no	JCS-WHT-2400S,2400FS,2400WS			





CARE AND CLEANING GUIDELINES

- * Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- \bigstar The product is heavy and it is recommended that two persons hold it while it is being fixed.

- * Carefully inspect the new product for damage before installation.
- ★ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- 🖈 Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance : EN 997 :2012+A1:2015



					• •			
PACKAGING DETAIL				LOADING PALLET DETAIL				
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)		No of pieces on pallet
400	400	560	30.5	1140	1140	2285		16
	JP UP							
Prepared By		Controlled By		Verified By	Approved By			
Designer		Quality control		Product Manager	Sanitaryware Head			
Date								
Revision/Version	1			Plotter Updated on	Month	22-Aug	Year	2019